VAISALA

Order form
Purchaser

valid from 01-10-2015
Order no.

TMW90 Temperature Transmitter - Current output

						1	2	3	4	5	6	7	8	9	
	Vaisala Temperature Transmitter				**TMW90**	**2**	**1**				**0**	**0**	**A**		**Price**
3	**Output scaling for temperature**	**-5...+55 ℃ (+23 ... +131 ℉)**						**A**							
		0...+60 ℃ (+32 ... +140 ℉)						**B**							
	SPECIAL	**Define**	**Low**	**High**				**X**							
4	**Display and colour**	**Non-display, Standard White (RAL9003)**		**STDWHITESOLID**					**0**						
		Display, Standard White (RAL9003)		**STDWHITEDISP**					**1**						
		Non-display, Black (RAL9005)		*BLACKSOLID*					*2*						
		Display,Black (RAL9005)		*BLACKDISPLAY*					*3*						
		Non-display,No logo, standard White (RAL9003)		*NOLOGOSTDSOLID*					*8*						
		Display, No logo, standard White (RAL9003)		*NOLOGOSTDDISPLAY*					*9*						
5	**Units**	**Metric**								**A**					
		Non metric								**B**					
9	**Quick reference guide**	**No manual**												**0**	
		Multilingual for analog devices												**2**	

Accessories:

TM10SP	Temperature module
219980	Connection cable for HM70 hand-held meter
219690	USB cable fro PC connection

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings:

TMW90	**2**	**1**	**A**	**0**	**A**	**0**	**0**	**A**	**2**

VAISALA

Order form
Purchaser

valid from 16-05-2012
Order no.

TMW90 Temperature Transmitter - Voltage output

						1	2	3	4	5	6	7	8	9	
	Vaisala Temperature Transmitter				**TMW90**	**3**							**A**		**Price**
2	**Output signal**	**0...10 V**	**3-wire**				**2**								
		0...5 V	**3-wire**				**3**								
3	**Output scaling for temperature**	**-5...+55 ℃ (+23 ... +131 ℉)**						**A**							
		0...+60 ℃ (+32 ... +140 ℉)						**B**							
	SPECIAL	**Define**	**Low** _____	**High** _____ ℃ (℉)				**X**							
4	**Display and colour**	**Non-display, Standard White (RAL9003)**		**STDWHITESOLID**					**0**						
		Display, Standard White (RAL9003)		**STDWHITEDISP**					**1**						
		Non-display, Black (RAL9005)		*BLACKSOLID*					*2*						
		Display,Black (RAL9005)		*BLACKDISPLAY*					*3*						
		Non-display,No logo, standard White (RAL9003)		*NOLOGOSTDSOLID*					*8*						
		Display, No logo, standard White (RAL9003)		*NOLOGOSTDDISPLAY*					*9*						
5	**Units**	**Metric**								**A**					
		Non metric								**B**					
6	**Relay operation**	**None**									**0**				
		Relay closed above set point									**1**				
		Relay closed below set point									**2**				
		Fault (Relay closed when transmitter in error state)									**F**				
		Not Fault (Relay closed when transmitter in normal operation)									**N**				
7	**Relay set-point and hysteresis**	**None**										**0**			
		Define special setpoint	**Low Limit:** _____	**High Limit:** _____ ℃ (℉)								**X**			
9	**Quick reference guide**	**No manual**												**0**	
		Multilingual for analog devices												**2**	

Accessories:

TM10SP	Temperature module
219980	Connection cable for HM70 hand-held meter
219690	USB cable fro PC connection

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings:

TMW90	**3**	**2**	**A**	**0**	**A**	**0**	**0**	**A**	**2**